

Part Type: FTLX1472M3BTL

FINISAR COMPATIBLE FTLX1472M3BTL Quick Spec:

Form Factor:	SFP+
TX Wavelength:	1310nm
Reach:	10km
Cable Type:	SMF
Rate Category:	10GBase
Interface Type:	LR
DDM:	Yes
Connector Type:	Dual-LC
Power Budget:	6.00 dB
TX Power Min/Max:	-8.00 to 0.50
RX Power Min/Max:	-14.00 to -3.0



FINISAR COMPATIBLE FTLX1472M3BTL Features

- Operating Data Rate up to 10.3Gbps
- 1310nm DFB-LD Transmitter
- Single 3.3V Power Supply and TTL Logic Interface
- Hot Pluggable
- Compliant with MSA SFP+
- Compliant with IEEE 802.3ae 10GBASE-LR
- Compliant with IEEE 802.3ae 10GBASE-LW
- Compliant with SFF-8472
- RoHS 6 Compliant
- Operating Case Temperature:
 - Standard 0 to 70 C
 - Industrial -40 to +85 C

FINISAR COMPATIBLE FTLX1472M3BTL Applications

- 10GBASE-LR at 10.3125Gbps
- 10GBASE-LW at 9.953Gbps
- Other Optical Links

FINISAR COMPATIBLE FTLX1472M3BTL Electrical Characteristics (Condition: Ta=TOP)

Parameter	Symbol	Min.	Typ	Max.	Unit	Notes
CML Inputs(Differential)	Vin	150		1200	mV p-p	AC coupled inputs
Supply Current	ICC			300	mA	
Input Impedance (Differential)	Zin	85	100	115	ohm	Rin > 100 kohm @ DC
Tx_Disable Input Voltage - Low	VIL	0		0.8	V	
Tx_Disable Input Voltage - High	VIH	2.0		3.45	V	
Tx_Fault Output Voltage - Low	VOL	0		0.5	V	
Tx_Fault Output Voltage - High	VOH	2.0		Vcc+0.3	V	
CML Outputs (Differential)	Vout	350		700	mV pp	AC coupled outputs
Output Impedance (Differential)	Zout	85	100	115	ohms	
Rx_LOS Output Voltage- Low	VOL	0		0.5	V	
Rx_LOS Output Voltage- High	VOH	2.5			V	

FINISAR COMPATIBLE FTLX1472M3BTL Optical Characteristics (Condition: Ta=TOP)

TX						
Parameter	Symbol	Min	Typ	Max	Unit	
Data Rate		-	10.3	-	Gb/s	
gum Core Diameter SMF			10		Km	
Centre wavelength	λ_c	1270	1310	1355	nm	
Output Spectral Width(-20dB)	$\Delta\lambda$	-	-	1	nm	
Average Output Power	P _{out}	-8	-	+0.5	dBm	
Extinction Ratio	ER	3.5	-	-	dB	
Average Power of OFF Transmitter				-30	dBm	
Side Mode Suppression Ratio	SMSR	30			dB	
Input Differential Impedance	Zin	90	100	110	Ω	
TX Disable	Disable		2.0	Vcc+0.3	V	
	Enable		0	0.8		
TX Fault	Fault		2.0	Vcc+0.3	V	
	Normal		0	0.8		
Tx Disable Assert Time	t _{off}			10	us	



Build It Bigger. Build It Faster. Build It Sooner.

FINISAR COMPATIBLE FTLX1472M3BTL

Dual-LC, 1310nm, SMF, 10km

RX					
Parameter	Symbol	Min	Typ	Max	Unit
Center Wavelength	λ_c	1260		1565	nm
Receive Sensitivity	P_{in}	-	-	-14	dBm
Maximum Input Power	P_{MAX}	-3	0	-	dBm
Signal Detect Threshold-Assertion:	SD_{HIGH}	-	-	-15	dBm
Signal Detect Threshold-Deassertion:	SD_{LOW}	-25	-	-	dBm
Output Differential Impedance	P_{in}	90	100	110	Ω
Receiver Overload	P_{max}	0.5			dBm
Optical Return Loss	ORL			-12	dB
LOS	High	2.0		$V_{cc}+0.3$	V
	Low	0		0.8	

Absolute Maximum Ratings ($T_c=25^\circ C$)

Parameter	Symbol	Min	Max	Unit
Storage Temperature	T_{ST}	-40	+85	$^\circ C$
Operating Temperature (Com)	T_{IP}	0	+70	$^\circ C$
Operating Temperature (Ext)		-40	+85	
Input Voltage	T_{CC}	0	5	V

FINISAR COMPATIBLE FTLX1472M3BTL Recommend Operation Environment

Parameter	Symbol	Min	Typ	Max	Unit
Supply Voltage	V_{cc}	+3.15	3.3	+3.45	V
Operating Temperature	T_{OP}	0	-	+70	$^\circ C$
Operating Temperature		-40	-	+85	